

Subdivision of Tp. 31 North, Range 51 E. M. D. M.

- 39.00 Enter juniper timber, bears N. and S.
- 40.00 Set a sandstone 16 X 10 X 8 ins. 10 ins. in the ground marked 1/4 on North face for 1/4 section cor. Raised a mound of stone 3 1/2 ft. base, 1 1/2 ft. high, North of cor., from which corner a juniper 8 inches in dia. bears S. 33° 15' E. 30 lks. dist. marked 1/4 S. 25 B X T. a juniper 12 ins. in dia. bears N. 85° 45' E. 18 lks. dist. marked 1/4 S X 24 B X T.
- 41.50 Top of spur 38 ft. above draw, course S. E. and N. W. Descend.
- 51.80 Ravine 120 ft. below top of spur, course N. 40° E. Ascend.
- 57.80 Top of spur 60 ft. above draw, bears N. E. and S. W. Descend.
- 61.50 Head of ravine 25 ft. below top of spur, course N. E. Ascend
- 65.20 Top of spur 50 ft. above ravine bears N. E. and S. W. Descend
- 78.80 Draw 90 ft. below top of spur, course N. 50° E. Ascend.
- 80.05 Intersect E. boundary at a point 70 lks. N. 0° 2' W. of corner of Secs. 19 & 30 at point of intersection I set a sandstone 18 X 12 X 10 ins. 12 ins. in the ground marked G X G X on W. 2 *grooves* on S. and 4 *grooves* on N. faces, raised a mound of stone 5 ft. base, 2 1/2 ft. high, W.