

Subdivision of Tp. 31 N., R. 51 East, M. DM.

- 80.00 Intersect E. boundary 200 lks. N. ^{0° 2' W.} of cor. of Secs. 7 and 18. At point of intersection set a sand stone 8 X 12 X 10 ins. in mound of stone marked C. C. on W., 4 grooves on S. and 2 grooves on N. faces. Raised a mound of stone, 4 ft. base, 2 ft. high, west of cor. Pits impracticable.
- Land mountainous; soil 3rd rate, with growth of sage brush and bunch grass. No timber.
- Mountainous land, 80 chs.
- July 15, 1904.
-
- 40.00 North ^{0° 1' W.} on a random line between Secs. 11 and 12. Set a temporary 1/4 Sec. cor.
- 78.50 Intersect E. and W. line at a point 10 lks. East of Sec. Cor. of Secs. 1, 2, 11 ^{and} 12, which is an old decayed post in mound of earth; reestablish corner by setting a basalt stone 18 X 12 X 10 ^{ins.} 12 ins. in the ground marked 5 notches on S. and 1 notch on E. ^{edges.} Dug pits 18 X 18 X 12 ins. in each section.
- Raised a mound of earth and stone, 4 ft. base, 2 ft. high, west of corner. Thence I run S. 0° 4' E. on a true line. Ascend.
- 23.00 Top of spur 250 ft. above Sec. Cor. bears N. 40° E. and S. 40° W. Descend.