

Subdivision of T. 20 N. R. 44 E. M. D. M.

Survey Commenced May 4, 1905 and executed with a Leitz transit n^o 1882 having two double verniers placed opposite to each other and reading to 1' of an arc.

The instrument was tested on the true meridian at San Francisco, Calif. and found correct per Certificate dated August 19, 1904.

Starting at the Cor. of Secs. 1, 2, 35 $\frac{1}{2}$, 36 on the S. bdy. of the township, reference is made to the field notes of the re-survey of the South bdy. of this tp. for a description of this Cor. and a record of the observation from which these lines were deflected.

Thence I run

N 0° 01' N. bet. Secs. 35 $\frac{1}{2}$ & 36.

ascending

7.30 top of steep ascent, thence over rough broken stony hills.

15.64 fence bears S 80° E and N 80° W.

21.65 Head of ravine 50 yds wide Course S 30° E.

32.70 top of ridg bears N. E. and S 20° W. and descend.

40.00 Set granite stone 18x7x4 ins. 12 ins in the ground for $\frac{1}{4}$ Sec. Cor. Marked $\frac{1}{4}$ on N. face raise mound of stone 3 $\frac{1}{2}$ ft. base 1 $\frac{1}{2}$ ft. high N. of Cor.