

52. 196

Subdivision of T. 20 N. R. 44 E. M. & M.

Chaus.

bluffs and ascend.

74.60 Spur bears S. and descend

80.16 The Cor. of Secs. 29, 30, 31⁴ & 32.

Land Mountainous

Soil 4th rate stony

No timber, sage brush

Mountainous land 80.16 chs.

June 1, 1905.

West on true line bet. Secs. 30⁴ & 31
descending along steep southerly slope

3.00 Spur bears S.W. and descend abruptly

8.25 ravine 3 chs. wide Course S.W. and descend

14.71 Spur bears S.W. and descend along steep
southerly slope.

40.00 Set quartzite stone 20x6x5 in. 15 in. in
the ground for $\frac{1}{4}$ sec. Cor. marked $\frac{1}{4}$ on N.
face, raise mound of stone $3\frac{1}{2}$ ft. base $1\frac{1}{2}$
ft. high N. of Cor. bend in Amador Cañon
bears S. 1 ch. dist. and ascend along steep
S. slope.

69.75 Spur bears S. and descend.

73.55 Shaft 6x4 ft. 15 ft. deep. bears N. 25 chs. dist.

78.30 road bears N⁴ & S.

83.70 Intersect N. bdy. of Tp. 10. 39 chs. S 0° 03' E. of
Cor. of Secs. 25⁴ & 36. Set granite stone 28x6x4
in. 21 in. in the ground for closing Cor. of