

Subdivision of T. 16 N. R. 43 E. M. D. M.

Chains.

- West on true line bet. Secs. 30²/₄ & 31.
 descending steep mountain
- 24.30 Stream 1/2 k. wide in Cañon Course N 60° W
 and as end.
- 40.00 Set slate stone 18 x 7 x 4 ins. 12 ins. in the
 ground for 1/4 sec. Cor. marked 1/4 on N.
 face, raise mound of stone 3 1/2 ft. base
 1 1/2 ft. high N. of Cor.
- 54.90 High rocky spur bears N 30° W. and descend
- 62.47 Stream 1/2 k. wide in ravine Course N 10° W
 and as end.
- 80.34 Intersect Reese River Guide Meridian, N.
 bdy. of Tp. 5.39 Ch. S. of Cor. of Secs.
 25²/₄ & 36 Set lime stone 18 x 6 x 5 ins
 12 ins. in the ground for closing corner
 of Secs. 30²/₄ & 31 marked CC on E. with
 5 grooves on N. and 1 groove on S. face.
 raise mound of stone 4 ft. base 2 ft. high
 E. of Cor.
- Land mountainous
 Soil 3rd rate stony.
 Timber, scattering Pine & Mahogany,
 good mountain bunch grass.
- Mountainous land 80.34 Chs.

July 17, 1905.

N 0° 03' W. on true line bet. Secs. 29²/₄ & 30.