

Subdivisions of T. 21 N., R. 24 E.

Thence

N. $0^{\circ}09'$ W. on true line bet. Secs.

3rd and 4th ^{Continue measurement} over rolling land

40.00

At point 34.4 chs. N. $0^{\circ}09'$ W. from the cor. of Sec. 3rd and 4th here to fore described, I set a Basalt Stone $15 \times 8 \times 8$ ins. - 10 ins. in ground for $\frac{1}{4}$ sec. cor. marked with $\frac{1}{4}$ on W. face and raise a mound of stone 3 ft. base $1\frac{1}{2}$ ft. high $\frac{1}{4}$ of cor.

Pits impracticable

29.00

Commence ascent of mountain

83.55

Intersect N. Edy. of T. p. 3, 24 chs.

N. $89^{\circ}55'$ W. of witness cor. of Secs. 33rd and 34th here to fore described

At point of intersection I set a Basalt rock $18 \times 8 \times 8$ ins. 12 ins. in ground for closing cor. of Secs. 3rd and 4th marked with 3 quarters ^{on} E. and W. and CC on S. face. ¹ and raise a mound of stone 4 ft. base 2 ft. high S. of cor.

Pits impracticable

Land mountainous and rolling
Soil 1st and 3rd rate.