

Subdivisions of N. 2 T. 20 N., R. 23 E.

- Chs. N. 0° 02' W. on true line bet. 0.  
Secs. 3<sup>and</sup> 4 over mountainous  
land, desc. steep slope
- 33.00 Prairie, Course NE, asc.
- 40.00 on SW. slope, set a basalt  
stone 20 x 10 x 6 ins. - 15 ins.  
in ground for  $\frac{1}{4}$  sec. cor.  
mark with  $\frac{1}{4}$  on W. face  
and raise a mound of stone  
3 ft. base 2 ft. high W. of cor.  
Pits impracticable
- 48.20 Top of Spar or ridge bears  
NE. and SW., desc.
- 79.00 Work, Course NE.
- 79.64. Intersect N. body of top. 2.35 Chs.  
N. 89° 14' E. from the Std. Cor. of  
Secs. 33<sup>and</sup> 34. heretofore described  
At point of intersection set  
a basalt stone 20 x 12 x 8 ins. -  
14 ins. in ground for closing  
cor. of secs. 3<sup>and</sup> 4. mark with  
3 grooves on E. and W. and C.C.  
on S. faces; raise a mound  
of stone 3 ft. base 2 ft. high  
S of cor.  
Pits impracticable  
Land mountainous