

Subdivision of T. 25 N. R. 28 E.

Chairs

- 44.00 Dry wash course NW.
 39.98 Set a granite stone 14x10x10 in
 in the ground for $\frac{1}{4}$ sec. cor.
 marked $\frac{1}{4}$ on N. face. and raise a
 mound of stone 2 ft. face $1\frac{1}{2}$
 ft. high N of cor.
 Pits impracticable.
 44.10 Dry wash course NW.
 43.60 Dam wash course S 70° W.
 51.50 Dam wash course N 70° W.
 60.50 Dam dry wash course SW.
 79.96 The cor. of secs. 3, 4, 9 and 10
 Land rolling
 Soil sandy 31 raw
 Chg. brush and grass

N. 0° 1' W. bet. secs. 3 and 4
 Poor rolling land.

- 40.00 Set a volcanic stone 16x15x8 in
 in the ground for $\frac{1}{4}$ sec. cor. marked
 $\frac{1}{4}$ on W. face dig pits 18x18x12 in.
 N and S of stone 3 ft. dist. and raise a
 mound of earth $3\frac{1}{2}$ ft. face $1\frac{1}{2}$ ft. high
 N of cor.
 77.30 Intersect 5th standard parallel
 North at 3.26 chs. E. of the