

Retracement of E. bdy. of T. 44 N., R. 56 E.

Chains

Preliminary to commencing the subdivision of T. 44 N., R. 56 E., in accordance with instructions from the surveyor general, I retrace the E. bdy. of the township as follows.

The S.E. cor. of T. 44 N., R. 56 E. is a quartzite stone 7x6x8 ins. above ground, firmly set and marked and witnessed as described by the surveyor general.

Thence I run,

N. on the E. bdy. of sec. 36.

10.70 The cor. of Tps. 43 and 44 N., R. 57 E., which is a basalt stone, set in a mound of stone, and marked and witnessed as described by the surveyor general.

51.60 The 1/4 sec. cor. which is a basalt stone, 14x7x6 ins. set in a mound of stone, and marked and witnessed as described by the surveyor general.

92.27 The cor. of secs. 25, 30, 31 and 36, which is a granite stone, firmly set in a mound of stone, and marked and witnessed as described by the surveyor general.

From the cor. of secs. 25, 30, 31 and 36,

I run,

N. on the E. bdy. of sec. 25.

40.17 The 1/4 sec. cor. bears W. 40 lks. and is a basalt stone, firmly set in a mound of stone, and marked and witnessed as described by the surveyor general.

The bearing of the last 1/2 mile is N. 0° 34' W.

I continue my line N.

80.25 The cor. of secs. 19, 24, 25 and 30, bears W. 88 lks. and is a basalt stone, firmly set in a mound of stone, and marked and witnessed as described by the surveyor general.

The bearing of the last 1/2 mile is N. 0° 41' W.

From the cor. of secs. 19, 24, 25 and 30,

I run N.