

Retracement of the E. bdy. of T. 44 N., R. 56 E.

Chains.

is a basalt stone, firmly set in a mound of stone, and marked and witnessed as described by the surveyor general. The bearing of the last 1/2 mile is N. 0° 22' W.

From the cor. of secs. 1, 6, 7 and 12,

I run,

N. on the E. bdy. of sec. 1.

40.04 The 1/4 sec. cor. bears W. 23 lks. and is a basalt stone, 7x5x7 ins. above ground, firmly set, and marked and witnessed as described by the surveyor general.

The bearing of the last 1/2 mile is N. 0° 20' W.

I continue my line N.

79.82 The cor. of Tps. 44 and 45 N., Rs. 56 and 57 E. bears W. 42 lks., and is a basalt stone, firmly set in a mound of stone, marked and witnessed as described by the surveyor general.

The bearing of the last 1/2 mile is N. 0° 16' W.

September 24. 1906.

From the cor. of Tps. 44 and 45 N., Rs. 56 and 57 E.

I retrace the N. bdy. of Tp. 44 N. R. 56 E. as follows.

W. on the S. bdy. of sec. 36

40.18 The 1/4 sec. cor. which is a basalt stone, 15x5x12 ins. above ground, firmly set, and marked and witnessed as described by the surveyor general.

The bearing of the last half mile is West.

I continue my line W.

80.41 The cor. of secs. 1, 2, 35 and 36 bears S. 70 lks. and is a quartzite stone, 10x6x8 ins. above ground, firmly set, and marked and witnessed as described by the surveyor general.

The bearing of the last half mile is S. 89° W.

From the cor. of secs. 1, 2, 35 and 36,

I run,