

Subdivision of T. 44 N., R. 56 E.

29

Chains.

- From the cor. of secs. 27, 28, 33 and 34,
I run,
S. 0° 2' E. bet. secs. 33 and 34.
Through scattering sage brush, ascend 32° slope.
- 5.00 Top of spur, 175 ft. above sec. cor., bears N.E. and S.W.
Descend.
- 12.00 Head of ravine, 75 ft. below top of spur, course N.E.;
ascend.
- 17.00 Top of ridge, 75 ft. above ravine, bears E. and W. ;
descend.
- 25.00 Top of rocky spur, slopes E.
- 40.00 Set a quartzite stone, 17x9x6 ins., 4 ins. in the ground,
on bed rock, in a mound of stone, for $\frac{1}{4}$ sec. cor.,
marked $\frac{1}{4}$ on W. face; and raise a mound of stone, 2 ft.
base, $1\frac{1}{2}$ ft. high, W. of cor. Pits impracticable.
This cor. is 250 ft. below top of ridge.
- 42.80 Ravine, 50 ft. below $\frac{1}{4}$ sec. cor., course S. 30° W.;
ascend.
- 49.00 Top of spur, 50 ft. above ravine, bears N.E. and S.W.;
descend.
- 55.40 Ravine, 100 ft. below top of spur, course W.; ascend.
- 69.00 Top of spur, 150 ft. above ravine, bears N.E. and S.W.;
descend.
- 84.40 Ravine, 200 ft. below top of spur, course S.W.; ascend,
100 ft. to
- 93.15 Intersect S. bdy. of the Tr. 10.73 chs. W. of the cor.
of secs. 3, 4, 33 and 34, which is a quartzite stone,
10x3x5 ins. above ground, marked and witnessed as
described by the surveyor general. I destroy all marks
relating to secs. 33 and 34, and at the point of inter-
section; set a quartzite stone, 18x10x6 ins., 6 ins. in
the ground, on bed rock, in a mound of stone, for clos-
ing cor. of secs. 33 and 34, marked C C on N., with 3
grooves on E. and W. faces; and raise a mound of stone,
2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor. Pits impracticable.