

Subdivision of T. 44 N., R. 56 E.

Chains.
19.30 Dry creek bed, course S.W., comes from E.; ascend.
40.00 Set a quartzite stone, 14x12x11 ins., 9 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on W. face; and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor. Pits impracticable.
52.00 Ravine, course W.
54.50 Top of spur. bears E. and W.
55.65 Wire fence, bears N. 70° E. and S. 70° W.; leave field.
57.00 Ravine, 20 ft. deep, course W.
72.00 Top of spur, 100 ft. above ravine, bears E. and W. ;
74.75 Ravine, 15 ft. deep, course W.
93.21 Intersect S. bdy. of the Tp. 10.48 chs. W. of the cor. of secs. 4, 5, 32 and 33, which is a conglomerate stone, 10x3x6 ins. above ground, marked and witnessed, as described by the surveyor general. I destroy all marks on this cor. relating to secs. 32 and 33.
At the point of intersection, I set a conglomerate stone, 18x8x7 ins., 12 ins. in the ground, for closing cor. of secs. 32 and 33, marked C C on N., with 4 grooves on E. and 2 grooves on W. face; and raise a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor. Pits impracticable.
Land, hilly.
Soil, sandy and rocky, 3rd. and 4th. rate.
Undergrowth, sage brush, willow and bunch grass.
No timber.

From the cor. of secs. 28, 29, 32 and 33,
I run,
N. 0° 3' W. bet. secs. 28 and 29.
Through scattering sage brush, ascend.
3.00 Top of spur, 20 ft. above sec. cor., Bears E. and W.; descend.
6.50 Ravine, 25 ft. below top of spur, course W.; ascend.
15.00 Top of spur, 75 ft. above ravine, bears E. and W.; descend.