

Subdivision of T. 44 N., R. 56 E.

Chains.
 23.50 Ravine, 75 ft. deep, course N.W.

40.00 Set a granite stone, 16x10x10 ins., 11 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on N. face; and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, N. of cor. Pits impracticable.

56.25 Top of rocky bluff, 10 ft. high; descend.

62.10 Wagon road, from Gold Creek to Bruneau, bears N.W. and S.E.; enter flat, 75 ft. below top of bluff.

67.00 Dry channel of Hay Meadow creek, course N.W.

67.80 Another dry channel of Hay Meadow creek, course N.W. ascend about 15 ft. to

69.99 Intersect Ruby Valley Guide Meridian, 14.09 chs. N. of the cor. of secs. 19 and 30, which is a granite stone, 9x6x7 ins. above ground, firmly set, and marked and witnessed as described by the surveyor general. At the point of intersection, set a quartzite stone, 18x12x6 ins., 12 ins. in the ground for closing cor. of secs. 19 and 30, marked C C on E.; with 4 grooves on N., and 2 grooves on S. face; and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, E. of cor. Pits impracticable.

I destroy all markings on the original Ruby Valley Guide Meridian cor. referring to secs. 19 and 30, leaving it as a monument of alignment only.

Land, rolling.

Soil, sandy and rocky, 3rd. and 4th. rate.

Undergrowth, sage brush, willows, rye and bunch grass.

No timber.

N. 0° 4' W. bet. secs. 19 and 20.

Through scattering sage brush, ascend over rolling land.

23.00 Draw, course W.; ascend 100 ft. to

40.00 Set a granite stone, 16x11x6 ins., 11 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on W. face; and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.