

Subdivision of T. 44 N., R. 56 E.

Chains.

- 49.40 Old placer mining ditch, 20 lks. wide, bears N. 30° W. and S. 30° E.
- 52.64 Wire fence, bears N. 20° W. and S. 20° E.; leave field.
- 53.25 Wagon road, from Mountain City to Elko, bears N. 20° W. and S. 20° E.
- 70.74 Intersect the Ruby Valley Guide Meridian, 15.15 chs. N. of the old cor. of secs. 7 and 18, which is a quartzite stone, 7x7x5 ins. above ground, firmly set, and marked and witnessed as described by the surveyor general. At the point of intersection, set a quartzite stone, 18x8x6 ins., 12 ins. in the ground, for closing cor. of secs. 7 and 18, marked C C on E. with 2 grooves on N. and 4 grooves on S. face; and raise a mound of stone, 2 ft. base, 1½ ft. high, E. of cor. Pits impracticable. I destroy all markings on the original Ruby Valley Guide Meridian cor. referring to secs. 7 and 18, leaving it as a monument of alignment only.
- Land, rolling.
- Soil, rocky, 4th. rate.
- Undergrowth, sage brush, willows and bunch grass.
- No timber.

N. 0° 4' W. bet. secs. 7 and 8.

Through scattering sage brush, over rolling land.

- 10.00 From this point, a post marked U.S.S. 4 (or 7) 1756, bears S. 62° 34' W. 58 ft. dist.

- 19.00 Ravine, 15 ft. deep, course E.

- 31.98 Wagon road, from Gold Creek to Martin's canyon, bears N.W. and S.E.

- 36.00 Ravine, 25 ft. deep, course S. 60° E.

- 36,50 Wagon road, from Gold Creek, to Martin's canyon, bears N.E. and S.W.

- 40.00 Set a granite stone, 14x11x7 ins., 9 ins. in the ground, for ¼ sec. cor.; marked ¼ on W. face; and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.