

First Standard Parallel South, through Range 46 East.

Chains

I groove on E. and 5 grooves on W. faces, and raise a mound of stone 2 ft. base  $1\frac{1}{2}$  ft. high N. of cor. Pits Impracticable.

Land mountainous.

Soil rocky, 4th. rate.

Scattering sagebrush.

Mountainous land, 80.00 chs.

S.  $89^{\circ}58'$  E. on secant S. of sec. 36.

Over mountainous land.

26. 30 Road bears NE. and SW.

28. 00 Dry wash, course SW.

Difference between measurements of 40.00 chs. by two sets of chainmen, is 4 lks.; position for middle point

By 1st. set, 39. 98 chs.

By 2nd. set, 40. 02 chs. the mean of which is

40.00 At apoint I. <sup>16</sup> ~~15~~ ft. N. of secant

Set a basalt stone 12X10X6 ins. 8 ins. in the ground, for std.  $\frac{1}{4}$  sec. cor. marked SC  $\frac{1}{4}$  on N. face, and raise a mound of stone 2 ft. base  $1\frac{1}{2}$  ft. high N. of cor.

Pits impracticable.

61.00 Low ridge, bears NE. and SW.

67.00 Dry wash, course SW.

Difference between measurements of 80.00 chs. by two sets of chainmen is 4 lks.; position for middle point

By 1st. set, 80.02 chs.

By 2nd. set, 79.98 chs.; the mean of which is

80.00 At a point 2. <sup>56</sup> ~~50~~ ft. N. of secant

Set a basalt stone 22X 14X6 ins. 17 ins. in the ground, for std. cor. of Tp. 4 S. Rgs. 46 and 47 E.; marked SC 45 on N. with 6 grooves on N.E. and W. faces.

47 E. on E. 46 E. on W. faces, and raise a mound of stone 2 ft. base,  $1\frac{1}{2}$  ft. high N. on cor. Pits impracticable.

Land mountainous.

Soil rocky, 4th. rate.