

32
10

9

First Standard Parallel South, through Range 47 East.

Chains	
70.20	Road bears NW. and SE.
71.00	Ravine, course NW. Ascend.
	Difference between measurements of 80.00 chs. by two sets of chainmen, is 8 lks. ; position for middle point
	By 1st. set, 80.04 chs.
	By 2nd. set, 79.96 chs.; the mean of which is
80.00	Set a basalt stone 16X12X10 ins. 11 ins. in the ground for std. cor. of secs. 35 and 36, marked S on N. with 1 groove on E. and 5 grooves on W. faces, and raise a mound of stone 2 ft. base, 1 1/2 ft. high, N. of cor. Pits impracticable.
	Land mountainous.
	Soil rocky, 4 th. rate.
	Sparse vegetation.
	Mountainous land, 80.00 chs.
	S. 89°58'E. on secant S. of sec. 36
	Over mountainous land. Ascending.
2.00	Ridge bears NE. and SW. Descend.
6.00	Road in ravine, course NE. Ascend.
27.00	Spur slopes NE. Descend.
29.00	Prospect hole bears S. 1.50 chs.
29.50	Ravine, course NE. Ascend.
39.00	Spur slopes NE. Descend over steep NE. slope.
	Difference between measurements of 40.00 chs. by two sets of chainmen, is 8 lks. ; position for middle point
	By 1st. set, 39.96 chs.
	By 2nd. set, 40.04 chs.; the mean of which is
40.00	At a point 1.15 ^{.15} ft. N. of secant
	Set a basalt stone 12X10X8 ins. 8 ins. in the ground for std. 1/2 sec. cor., marked SC 1/4 on N. face, and raise a mound of stone 2 ft. base, 1 1/2 ft. high, N. of cor. Pits impracticable.
70.00	Foot of steep descent, thence over gradual descent.