

Range Line between Ranges 47 and 48 E., through T. 10 S.

Chains	Soil sandy, 3rd. rate. Greasewood.
	South between secs. 25 and 30. Over rolling land.
10.00	Enter dry wash, course N. thence NW.
18.00	Leave dry wash.
40.00	Set a basalt stone 14X8X6 ins. 9ins. in the ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on W. face, and raise a mound of stone 2ft. base $1\frac{1}{2}$ ft. high W. of cor. Pits impracticable.
80.00	Point for sec. cor. falls in dry wash, course SW. Set a basalt stone 12X8X6 ins. 8 ins. in the ground for cor. of secs. 25, 30, 31, and 36, marked with 5 notches on N. and 1 notch on S. edges, and raise a mound of stone 2ft. base $1\frac{1}{2}$ ft. high W. of cor. Pits impracticable. Land rolling. Soil sandy and rocky, 4th. rate. Greasewood.
	South between secs. 31 and 36. Over rolling land.
13.90	Wagon road bears SE. and NW.
40.00	Set a basalt stone 12X10X6 ins. 8 ins. in the ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on W. face, and raise a mound of stone 2ft. base $1\frac{1}{2}$ ft. high W. of cor. Pits impracticable.
80.00	Set a basalt stone 20X14X8 ins. 15 ins. in the ground for cor. of Tps. 10 and 11 S. Rgs. 47 and 48 E., marked 10 S. on NE., 48 E. on SE., 11 S. on SW., and 47E. on NW. faces, with 6 notches on each edge, and raise a mound of stone 4ft. base 2ft. high S. of cor. Pits impracticable. Land rolling. Soil sandy and rocky, 3rd. and 4th. rate. Greasewood.