

Third Standard Parallel South through Range 45 E.

Chains.

68.00 Spur slopes SE.

72.00 Ravine course SE. Ascend.

Difference between measurements of 80.00 chs. by two sets of chainmen is 14 lks. position for middle point

By 1st. set, 80.07 chs.

By 2nd. set, 79.93 chs. the mean of which is

80.00 Set a basalt stone 12X10X8 ins. 8 ins. in the ground for std. cor. of secs. 31 and 32 marked S C on N. with 1 groove on W. and 5 grooves on E. faces, raise a mound of stone 2 ft. base 1 1/2 ft. high N. of cor. Pits impracticable

Land mountainous.

Soil rocky, 4th. rate.

Greasewood.

Mountainous land 80.00 chs.

S. 39°58' W. on secant S. of sec. 31.

Over mountainous land.

10.00 Spur slopes N. Descend.

14.00 Ravine course N. Ascend.

22.00 Spur slopes NE. Descend.

Difference between measurements of 40.00 chs. by two sets of chainmen is 12 lks. position for middle point

By 1st. set, 39.94 chs.

By 2nd. set, 40.06 chs. the mean of which is

40.00 At a point I. 13 ft. N. of secant

Set a basalt stone 18X14X8 ins. 12 ins. in the ground for std. 1/4 sec. cor. marked S C 1/4 on N. face and raise a mound of stone 2 ft. base 1 1/2 ft. high N. of cor. Pits impracticable.

45.00 Ravine course NE. Ascend.

61.00 Spur slopes NW.

Difference between measurements of 80.00 chs. by two sets of chainmen is 8 lks. position for middle point