

West Boundary T. 12 South Range 47 East.

Chains	
40.00	Set a basalt stone 14X12X6 ins. 9 ins. in the ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on W. face, and raise a mound of stone 2ft. base 1 $\frac{1}{2}$ ft. high W. of cor. Pits impracticable.
49.00	Ascend SW. slope of ridge.
65.50	Summit of ridge bears NW. and SE.
66.00	Descend over rocky ledges.
80.00	Set a basalt stone 14X12X6 ins. 9 ins. in the ground for cor. of secs. 7, 12, 13, and 18, marked with 2 notches on N. and 4 notches on S. edges, and raise a mound of stone 2ft. base 1 $\frac{1}{2}$ ft. high W. of cor. Pits impracticable Land mountainous. Soil rocky, 4th. rate. Greasewood. Mountainous land, 80.00 chs.
	North between secs. 7 and 12.
	Over rolling land. Descending.
9.00	Foot of ridge.
15.60	Telegraph line bears NE. and SW.
16.30	Road bears NE. and SW.
20.87	Pipe line bears NE. and SW.
40.00	Set a basalt stone 18X14X6 ins. 12 ins. in the ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on W. face, and raise a mound of stone 2ft. base 1 $\frac{1}{2}$ ft. high W. of cor. Pits impracticable.
80.00	Set a basalt stone 16X12X10 ins. 11 ins. in the ground for cor. of secs. 1, 6, 7, and 12, marked with 1 notch on N. and 5 notches on S. edges, and raise a mound of stone 2ft. base 1 $\frac{1}{2}$ ft. high W. of cor. Pits impracticable. Land rolling. Soil sandy, 3rd. rate. Greasewood.

North between secs. 1 and 6.