

FIRST STANDARD PARALLEL SOUTH, through RANGE 51 EAST.

CHAINS

post, 3 ft. dist., and raise a mound of earth, 3½ ft. base, 1½ ft. high, N. of cor.

Difference between measurement of 80.00 chs. by two sets of chainmen is 6 lks., position of middle point

By 1st. set 80.03 chs.,

By 2nd. set, 79.97 chs., the mean of which is

80.00

Set a charred pine post, 3 ft. long, 4 ins. sq., with marked stone, 24 ins. in the ground, for standard cor. of secs. 35 and 36 marked S C T 4 S R 51 E on N., S 35 on W. and S 36 on E. face, with 1 groove on E. and 5 grooves on W. faces, dig pits, 24x18x12 ins., crosswise on each line, E. and W. 3 ft. and N. of post 7 ft. dist., and raise a mound of earth 4 ft. base, 2 ft. high, N. of cor.

Land, rolling.

Soil, sandy, 3rd. rate.

No timber; undergrowth greasewood.

Dense undergrowth on 80.00 chs.

East, on S. bdy. of sec. 36.

Descend gradually over sandy land, through dense undergrowth.

Difference between measurement of 40.00 chs. by two sets of chainmen is 4 lks.,

position of middle point

By 1st. set, 39.98 chs.

By 2nd. set, 40.02 chs., the mean of which is

40.00

Set a charred pine post, 3 ft. long, 4 ins. sq., with marked stone, 24 ins. in the ground, for standard ¼ sec. cor., marked S C ¼ S 36 on N. face, dig pits, 18x18x12 ins., E. and W. of post, 3 ft. dist., and raise a mound of earth, 3½ ft. base, 1½ ft. high, N. of cor.

Difference between measurement of 80.00 chs. by two sets of chainmen is 6 lks., position of middle point

By 1st. set, 79.97 chs.,

By 2nd. set, 80.03 chs., the mean of which is