

EAST BOUNDARY T. 2 S., R. 50 E.

Chains

$\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on W. face; and raise a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high W. of cor. Pits impracticable.

51.00

Hollow, 350 ft. deep, drains W. Ascend abruptly.

80.00

Set a basalt stone 15x10x6 ins., 10 ins. in the ground, for cor. of secs. 1, 6, 7, and 12, marked with 1 notch on N. and 5 notches on S. edge; and raise a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high W. of cor. Pits impracticable.

Land, mountainous.

Soil, rocky, 4th rate.

Timber, scattering cedar and pinon pine.

Mountainous land 80.00 chs.

North, bet. secs. 1 and 6,

Ascending abruptly over rocky and mountainous land.

11.00

Divide Kawich Mts., bears NW. and SE.

Ascend abruptly.

40.00

Set a basalt stone 15x10x4 ins., 10 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on W. face; and raise a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high W. of cor. Pits impracticable.

52.00

Enter scattering cedar and pinon pine timber.

80.00

Set a basalt stone 18x12x6 ins., 12 ins. in the ground, for cor. of Tps. 1 and 2 S., Rs. 50 and 51 E., marked with 6 notches on each edge; from which

A pinon pine 6 ins. dia. bears N. 10° E. 16 lks. dist.

marked T 1 S R 51 E S 31 B T

A pinon pine 7 ins. dia., bears S. 10° E. 8 lks. dist.

marked T 2 S R 51 E S 6 B T

A pinon pine, 15 ins. dia., bears N. 45° W. 27 lks.

dist., marked T 1 S R 50 E S 36 B T