

SECOND STANDARD PARALLEL SOUTH, through RANGE 46 EAST.

CHAINS	
40.00	Set a basalt stone, 12x8x7 ins., 8 ins. in the ground, for standard $\frac{1}{4}$ sec. cor., marked S C $\frac{1}{4}$ on N. face, dig pits, 18x18x12 ins., E. and W. of stone, 3 ft. dist., and raise a mound of earth, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, N. of cor. Difference between measurement of 80.00 chs., by two sets of chainmen is 4 lks., position of middle point By 1st. set, 80.02 chs., By 2nd. set, 79.98 chs., the mean of which is
80.00	Set a basalt stone, 18x7x5 ins., 12 ins. in the ground, for standard cor. of secs. 31 and 32, marked S C on N., with 5 grooves on E. and 1 groove on W. faces, and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor. Pits impracticable. Land, rolling. Soil, rocky, 3rd. rate. No timber; undergrowth, greasewood. Dense undergrowth on 80.00 chs. <hr/> West, on S. Bdy. of sec. 31. Descend over rolling land, through dense undergrowth.
16.50	Wash, 1.00 ch. wide, 4 ft. deep, course SW. Difference bet. measurement of 40.00 chs., by two sets of chainmen is 6 lks., position of middle point By 1st. set, 40.03 chs., By 2nd. set, 39.97 chs., the mean of which is
40.00	Set a basalt stone, 18x12x6 ins., 12 ins. in the ground, for standard $\frac{1}{4}$ sec. cor., marked S C $\frac{1}{4}$ on N. face, and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor. Pits impracticable. Difference bet. measurement of 80.00 chs., by two sets of chainmen is 4 lks., position of middle point By 1st. set, 80.02 chs., By 2nd. set, 79.98 chs., the mean of which is
80.00	Set a basalt stone, 18x12x7 ins., 12 ins. in the ground, for standard cor. of Tps. 8 S., Rs. 45 and 46 E., marked