

EAST BOUNDARY OF T.7 S., R.44 E.

CHAINS

Mountainous land on 80.00 chs.

North, bet. secs. 7 and 12.

~~Ascend over rocky and mountainous land.~~

1.50 Begin abrupt ascent over sandstone ledges, bearing E. and W.

25.42 Top of ledges, 600 ft. high, bears E. and W.
Ascend.

36.00 Spur, projects W.

~~Descend.~~

40.00 Set a sandstone, 15x8x5 ins., 10 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on W. face, and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Pits impracticable.

80.00 Hollow, 150 ft. deep, course SW.

Set a sandstone, 15x8x5 ins., 10 ins. in the ground, for cor. of secs. 1-6-7 and 12, marked with 5 notches on S. and 1 notch on N. edges, and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
Pits impracticable.
Land, mountainous.

Soil, rocky, 3rd. and 4th. rate.

No timber.

Mountainous land on 80.00 chs.

North, bet. secs. 1 and 6.

Ascend abruptly over mountainous land.

20.00 Ridge, bears NE. and SW.

Descend.

40.00 Set a basalt stone, 15x12x4 ins., 10 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on W. face, and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Pits impracticable.

80.00 Set a basalt stone, 20x12x12 ins., 15 ins. in the ground, for cor. of Tps. 6 and 7 S., Rs. 44 and 45 E., marked 6 S on NE., 45 E on SE., 7 S on SW., and 44 E on NW. faces, with 6 notches on each edges, and raise a mound of stone, 2 ft.

See Conclusive Notes, Book H p. 6.