

THIRD STANDARD PARALLEL SOUTH, through RANGE 51 EAST.

CHAINS

mound of stone, 2 ft. base, 1½ ft. high, N. of cor.

Pits impracticable.

Difference between measurement of 80.00 chs., by two sets of chainmen is 4 lks., position of middle point

By 1st. set, 80.02 chs.,

By 2nd. set, 79.98 chs., the mean of which is

80.00 Set a basalt stone, 15x9x6 ins., 10 ins. in the ground, for standard cor. of secs. 32 and 33, marked S C on N., with 4 grooves on E. and 2 grooves on W. faces, and raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.

Pits impracticable.

Land, rolling.

Soil, sandy, 3rd. rate.

No timber, undergrowth, greasewood.

Dense undergrowth on 80.00 chs.

East, on S. bdy. of sec. 33.

Ascend over rolling land, through dense undergrowth.

.50 Wash, 75 lks. wide, 10 ft. deep, course SW.

2.25 Wash, 75 lks. wide, 10 ft. deep, course SW.

Difference between measurement of 40.00 chs., by two sets of chainmen is 6 lks., position of middle point,

By 1st. set, 40.03 chs.,

By 2nd. set, 39.97 chs., the mean of which is

40.00 Set a basalt stone, 15x12x10 ins., 10 ins. in the ground, for standard ¼ sec. cor., marked S C ¼ on N. face, and raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.

Pits impracticable.

59.00 Enter sandy wash, 20 ft. deep, course S.

70.00 Leave wash.

Difference between measurement of 80.00 chs., by two sets of chainmen is 10 lks., position of middle point

By 1st. set, 80.05 chs.,

By 2nd. set, 79.95 chs., the mean of which is

80.00 Set a granite stone, 15x12x8 ins., 10 ins. in the ground,