

THIRD STANDARD PARALLEL SOUTH, through RANGE 55 EAST.

CHAINS

~~Difference between measurement of 80.00 chs., by two sets of chainmen is 10 lks., position of middle point~~
~~By 1st. set, 80.05 chs.,~~
~~By 2nd. set, 79.95 chs., the mean of which is~~
 80.00 Set a basalt stone, 12x9x6 ins., 8 ins. in the ground, for standard cor. of secs. 32 and 33, marked S C on N., with 4 grooves on E. and 2 grooves on W. faces, dig pits, 24x18x12 ins., crosswise on each line, E. and W., 3 ft., and N. of stone, 7 ft. dist., and raise a mound of earth, 4 ft. base, 2 ft. high, N. of cor.

Land, rolling.

Soil, gravelly, 3rd. rate.

No timber; undergrowth, greasewood and bayonet trees.

Dense undergrowth on 80.00 chs.

East, on S. bdy. of sec. 33.

Over rolling land, through dense undergrowth.

~~Difference between measurement of 40.00 chs., by two sets of chainmen is 4 lks., position of middle point~~
~~By 1st. set, 40.02 chs.~~
~~By 2nd. set, 39.98 chs., the mean of which is~~
 40.00 Set a basalt stone, 15x9x5 ins., 10 ins. in the ground, for standard $\frac{1}{4}$ sec. cor., marked S C $\frac{1}{4}$ on N. face, dig pits, 18x18x12 ins., E. and W. of stone, 3 ft. dist., and raise a mound of earth, 3 $\frac{1}{2}$ ft. base, 1 $\frac{1}{2}$ ft. high, N. of cor.

~~Difference between measurement of 80.00 chs., by two sets of chainmen is 6 lks., position of middle point~~
~~By 1st. set, 79.97 chs.,~~
~~By 2nd. set, 80.03 chs., the mean of which is~~

80.00 Set a basalt stone, 12x9x6 ins., 8 ins. in the ground, for standard cor. of secs. 33 and 34, marked S C on N., with 3 grooves on E. and W. faces, dig pits, 24x18x12 ins., crosswise on each line, E. and W., 3 ft., and N. of stone, 7 ft. dist., and raise a mound of earth, 4 ft. base, 2 ft. high,

See Corrective Notes Book 7 p 12 [7.303]