THIRD STANDARD PARALLEL SOUTH, through RANGE 55 EAST.

CHAINS	
	East, on S.bdy. of sec.35.
	Ascend over rocky land, through dense undergrowth.
15.20	Limestone spur, projects SW.
	Descend.
	~~Difference between measurement of 40.00 chs., by two sets of chainmen is 8 lks., position of middle point~~
	~~By 1st. set, 40.04 chs.,~~
	~~By 2nd. set, 39.96 chs., the mean of which is~~
40.00	Seta limestone, 16x11x6 ins., 11 ins. in the ground, for standard ¼ sec. cor., marked S C ¼ on N. face, dig pits, 18x18x12 ins., E. and W. of stone, 3 ft. dist., and raise a mound ~~of earth, 3½ ft. base, 1½ ft. high, N. of cor.~~
57.00	Hollow, 50 ft. deep, course S.
	Ascend over rolling land.
	~~Difference between measurement of 80.00 chs., by two sets of chainmen is 12 lks., position of middle point~~
	~~By 1st. set, 80.06 chs.,~~
	~~By 2nd. set, 79.94 chs., the mean of which is~~
80.00	Set a limestone, 16x14x5 ins., 11 ins. in the ground, for standard cor. of secs. 35 and 36, marked S C on N., with 1 groove on E. and 5 grooves on W. faces, and raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.
	~~Pits impracticable.~~
	Land, rolling.
	Soil, gravelly and rocky, 3rd. rate.
	No timber; undergrowth, greasewood and bayonet trees.
	Dense undergrowth on 80.00 chs.

	East, on S.bdy. of sec.36.
	Ascend over rolling land, through dense undergrowth.
4.50	Wash, 1.00 ch. wide, 15 ft. deep, course SE.
15.00	Wash, 1.50 chs. wide, 15 ft. deep, course SE.
30.00	Enter wash, 10 ft. deep, course SE.
	~~Difference between measurement of 40.00 chs., by two sets~~

See Corrective Notes, Book "X" p. 14 [p. 305]