

THIRD STANDARD PARALLEL SOUTH, through R.55 $\frac{1}{2}$ EAST.

CHAINS

16.00 Wash, 1.00 ch. wide, 10 ft. deep, course SE.

~~Difference between measurement of 40.00 chs., by two sets of chainmen is 4 lks., position of middle point~~

~~By 1st. set, 40.02 chs.,~~

~~By 2nd. set, 39.98 chs., the mean of which is~~

40.00 Set a limestone, 14x12x5 ins., 10 ins. in the ground, for standard $\frac{1}{4}$ sec. cor., marked S C $\frac{1}{4}$ on N. face, and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, N. of cor.

Pits impracticable.

~~Difference between measurement of 80.00 chs., by two sets of chainmen is 6 lks., position of middle point~~

~~By 1st. set, 80.03 chs.,~~

~~By 2nd. set, 79.97 chs., the mean of which is~~

80.00 Set a limestone, 14x8x6 ins., 10 ins. in the ground, for standard cor. of secs. 32 and 33, marked S C on N., with 4 grooves on E. and 2 grooves on W. faces, and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, N. of cor.

Pits impracticable.

Land, rolling.

Soil, rocky, 3rd. rate.

No timber; undergrowth, greasewood and bayonet trees.

Dense undergrowth on 80.00 chs.

East, on S. bdy. of sec. 33.

Ascend, through dense undergrowth.

1.00 Begin abrupt ascent, bearing N. and S.

20.00 Begin ascent over broken limestone ledges, bearing N. and S.

Difference between measurement of 40.00 chs., by two sets of chainmen is 16 lks., position of middle point

By 1st. set, 40.08 chs.,

By 2nd. set, 39.92 chs., the mean of which is

40.00 Set a limestone, 16x9x5 ins., 11 ins. in the ground, for standard $\frac{1}{4}$ sec. cor., marked S C $\frac{1}{4}$ on N. face, and raise a

See Connection Notes Book "F" p. 16 [1306]