

## WEST BOUNDARY OF T.9 S., R.46 E.

## CHAINS

North, bet. secs. 7 and 12.

Over level land, through dense undergrowth.

31.50 Old road, bears NW. and SE.

40.00 Set a basalt stone, 12x8x6 ins., 8 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked  $\frac{1}{4}$  on W. face, dig pits, 18x18x12 ins., N. and S. of stone, 3 ft. dist., and raise a mound of earth,  $3\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

80.00 Set a basalt stone, 12x8x6 ins., 8 ins. in the ground, for cor. of secs. 1-6-7 and 12, marked with 5 notches on S. and 1 notch on N. edges, dig pits, 18x18x12 ins., in each sec., 5 ft. dist., and raise a mound of earth, 4 ft. base, 2 ft. high, W. of cor.

Land, nearly level.

Soil, sandy, 3rd. rate.

No timber: undergrowth, greasewood.

Dense undergrowth on 80.00 chs.

---

 North, bet. secs. 1 and 6.

Over level land, through dense undergrowth.

40.00 Set a basalt stone, 12x8x6 ins., 8 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked  $\frac{1}{4}$  on W. face, and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

Pits impracticable.

87.04 Intersect the Second Standard Parallel South, 6.40 chs. west of the Standard cor. of Tps. 8 S., Rs. 45 and 46 E., which is a basalt stone, 12x7x7 ins. above ground, marked and witnessed as returned under contract No. 251.

Set a basalt stone, 15x10x8 ins., 10 ins. in the ground, for closing cor. of Tps. 9 S., Rs. 45 and 46 E., marked C C 9 S on S., 45 E on W., and 46 E on E. faces, with 6 grooves on S., E. and W. faces, and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, S. of cor.

Pits impracticable.

Land, nearly level.

Soil, sandy, 3rd. rate.

No timber: undergrowth, greasewood.