

CORRECTIVE NOTES OF

THE THIRD STANDARD PARALLEL SOUTH, through RANGE 55 EAST.

CHAINS

N., with 5 grooves on W. and 1 groove on E. faces, and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.

Pits impracticable.

I destroy all traces of the original stan. sec. cor.

Note:

There is no change of topography on this line.

East, on S. Bdy. of sec. 36.

Difference between measurement of 40.00 chs., by two sets of chainmen is 16 lks., position of middle point

By 1st. set, 39.92 chs.,

By 2nd. set, 40.08 chs., the mean of which is

40.00 The original stan. 1/4 sec. cor. bears E. 9 lks. dist.

Set original stone, a limestone, 18x12x10 ins., 12 ins. in the ground, for stan. 1/4 sec. cor., marked SC 1/4 on N. face, and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.

Pits impracticable.

I destroy all traces of the original stan. 1/4 sec. cor.

Difference between measurement of 80.00 chs. by two sets of chainmen is 14 lks., position of middle point

By 1st. set, 80.07 chs.,

By 2nd. set, 79.93 chs., the mean of which is

80.00 The original stan. cor. of Ts. 12 S., Rs. 55 and 55 1/2 E., bears E. 10 lks. dist.

Set original stone, a limestone, 16x12x4 ins., 11 ins. in the ground, for stan. cor. of Ts. 12 S., Rs. 55 and 55 1/2 E., marked SC 12 S on N., 55 E on W., and 55 1/2 E on E, with 6 grooves on E., W. and N. faces, and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.

Pits impracticable.

I destroy all traces of the original stan. Tp. cor.

Note:

There is no change of topography on this line.

For Tippy see bk H p. 45 [p. 51]

For Tippy see bk H p. 45 [p. 51]