

Chains

- N.89°58'W. on a true line between secs. 12 and 13.
Over level sandy valley.
- 23.63 SW. cor. of vacant building or house, formerly known as "Griswolds' Store" bears N.33°48'W.
- 38.99 Intersect E. Bdy. of the Pyramid Lake Indian Reservation at a point from which the 22½ mile stone on said boundary bears N.19°30'W. 10.99 chs. dist.
Set a concretionary limestone 16x11x8 ins., 10 ins. in the ground for closing cor. of fracl. secs. 12 and 13, marked C.C. P.L.I.R. on W. face, S. 12 on N. and S.13 on S. face, dig pit 24x18x12 ins. 7 ft. W. of stone and raise a mound of earth 3½ ft. base, 1½ ft. high, midway between pit and corner.
-
- From the cor. of secs. 1, 2, 11 and 12, I run
- 40.00 S.89°58'E. on a random line between secs. 1 and 12.
Set a temporary ¼ sec. cor.
- 80.20 Intersect E. Bdy. of the township at cor. of secs. 1,6,7 and 12, heretofore described.
Thence I run
N.89°58'W. on a true line between secs. 1 and 12.
Over sandy valley land.
- 28.48 Intersections of roads, bear NE., NW., SE. and SW.
- 40.10 Set a concretionary limestone 17x14x3 ins. 10 ins. in the ground for ¼ sec. cor., marked ¼ on N. face, dig pits 18x18x12 ins. E. and W. of stone 3 ft. dist., and raise a mound of earth 3½ ft. base, 1½ ft. high, N. of cor.
- 50.12 Road to Mud lake, bears N.8°E. and S.8°W.
- 56.10 Road, bears S. 5°E. and N.5°W.
- 67.38 Intersect the E. Bdy. of the Pyramid Lake Indian Reservation at a point from which the 23½ mile stone on said boundary bears N.19°30'W. 6.00 chs. dist.
Set a concretionary limestone 13x12x8 ins., 8 ins. in the ground for closing cor. of fracl. secs. 1 and 12, marked C.C. P.L.I.R. on W. face, S.1 on N. and S.12 on S. face, dig pit 24x18x12 ins. W. of stone 7 ft. dist., and raise a mound of earth 3½ ft. base, 1½ ft. high, midway between pit and stone.
-
- At the point of intersection of the line between secs. 1 and 2 with the E. Bdy. of Pyramid Lake Indian Reservation from which the 24 mile stone on said boundary bears N.19°30'W. 351 chs. dist.,
Set a concretionary limestone 14x10x8 ins., 9 ins. in the ground for closing corner of fracl. secs. 1 and 2, marked C.C. P.L.I.R. on S. face, S.1 on E. and S.2 on W. face, and raise a mound of stone 2 ft. base, 1½ ft. high, S. of cor. Pits impracticable.
This corner is in center of old road bears E. and W.
Thence I run
N.0°1'W. between secs. 1 and 2.
- .93 Road, bears E. and W.
- 3.51 Set a basalt stone 13x11x7 ins., 8 ins. in the ground for ¼ sec. cor., marked ¼ on W. face, and raise a mound of stone 2 ft. base, 1½ ft. high, W. of cor. Pits impracticable.
- 5.20 Point from which SW. cor. vacant house bears S.47°27'E., owner unknown.
- 8.51 Ascent more rapid, line skirts bluffs on W. side of slough bottom.
- 26.44 Travelled road to "Nugent" bears NW. and SE.
- 38.51 Left bank of slough about 3 chs. E. of line.
- 51.32 Intersect S. Bdy. of Tp. 24 N., R. 23 E., at 11.41 chs. W. of cor. to secs. 35 and 36.
Set a basalt stone 16x9x6 ins., 9 ins. in the ground for closing cor. of secs. 1 and 2, marked C.C.