

## 2. Resurvey of a portion of West Bdy. of T.23 N., R.24 E.

## Chains

No signs or traces of old corner.  
Land, valley.  
Soil, sandy mostly, 2nd rate.  
No timber.

North between secs. 13 and 18.  
Over less sandy land, interspersed with occasional bare and small clay flats.

40.00 Set a basalt stone 14x10x8 ins., 9 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked  $\frac{1}{4}$  on W. face, dig pits 18x18x12 ins. N. and S. of stone 3 ft. dist., and raise a mound of earth  $3\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.  
No trace of old corner.

80.00 Set a lava stone 16x10x8 ins., 10 ins. in the ground for cor. of secs. 7, 12, 13 and 18, marked with 4 notches on S. and 2 notches on N. edges, dig pits 18x18x12 ins. in each sec.  $5\frac{1}{2}$  ft. dist., and raise a mound of earth  $3\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.  
No trace of old corner.  
Land, level valley.  
Soil, sandy and gravelly, 2nd rate.  
 $N\frac{1}{2}$  mile less sandy than  $S\frac{1}{2}$ , but more gravelly.  
No timber.

North between secs. 7 and 12.  
Over valley land.

10.00 Descend gradually towards hollow.

18.87 Old road, in hollow, course NW. Road bears NW. and SE.

40.00 Set a concretionary limestone 13x13x7 ins., 8 ins. in the ground for  $\frac{1}{4}$  sec. cor., marked  $\frac{1}{4}$  on W. face, dig pits 18x18x12 ins. N. and S. of stone 3 ft. dist., and and raise a mound of earth  $3\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.  
No trace of old corner.

80.00 Set a basalt stone 20x10x8 ins., 15 ins. in the ground for cor. of secs. 1, 6, 7 and 12, marked with 5 notches on S. and 1 notch on N. edge, dig pits 18x18x12 ins. in each sec.  $5\frac{1}{2}$  ft. dist., and raise a mound of earth  $3\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.  
No trace of old corner visible.  
Land, valley.  
Soil, sandy, 2nd rate.  
No timber.

North between secs. 1 and 6.

15.00 Ascent very gradual.

17.37 Old road, bears NE. and SW.

40.00 Set a limestone (concretionary in character) 14x14x6 ins. 9 ins. in the ground for  $\frac{1}{4}$  sec. cor., marked  $\frac{1}{4}$  on W. face, dig pits 18x18x12 ins., N. and S. of stone 3 ft. dist., and raise a mound of earth  $3\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.  
No trace of old corner. Still ascend.

52.00 Top of main ridge, course E. and W. about 150 ft. above slough. Descend.

80.00 Over level valley.

87.81 Intersect N. Bdy. of Tp. at 10.99 chs. W. of cor. to Tps. 24 N., Rs. 23 and 24 E., which is a wooden post 4x4 ins., 3 ft. above ground firmly set and marked as witnessed as described by U.S. Surveyor General.  
Set a basalt stone 18x9x6 ins., 12 ins. in the ground for closing cor. of Tps. 23 N., Rs. 23 and 24 E., marked with C.C. on S. face, with 6 grooves on S., E. and W. faces, dig pits 30x24x12 ins., crosswise on each