

6.

Subdivisions of T. 23 N., R. 24 E.

Chains

- 65.37 Ledge of basaltic rock, 20 ft. high, bears E. and W.
 68.87 Top of ledge, and ridge top, bears NE. and SW.
 Descend.
 76.00 Center of hollow, course SW. about 50 ft. below
 last ridge, ascend.
 80.00 Set a volcanic stone 22x14x3 ins., 15 ins. in the
 ground, for cor. of secs. 5, 6, 7 and 8, marked with
 5 notches on S. and 5 notches on E. edge, dig pits
 18x18x12 ins. in each sec. $5\frac{1}{2}$ ft. dist., and raise a
 mound of earth $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
 Land, 1st half valley bench.
 Soil, stony and gravelly 2nd rate.
 Last half, mountainous 40 chs.
 Soil, 3rd rate and 4th rate, rocky and stony.
 No timber.
-
- 40.00 S. $89^{\circ}59'$ W. on a random line between secs. 6 and 7.
 Set a temporary $\frac{1}{4}$ sec. cor.
 78.77 Intersect West boundary of the township 2 lks. S. of
 the cor. to secs. 1, 6, 7 and 12, heretofore described.
 Thence I run
 East on a true line between secs. 6 and 7.
 Cross valley land.
 18.86 Road to Mud Lake, bears N. 17° W. and S. 15° E. at foot of
 bench; ascent gradually.
 38.77 Set a basalt stone 13x8x5 ins., 8 ins. in the ground
 for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on N. face, dig pits
 E. and W. of stone 3 ft. dist., and raise a mound
 of earth $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
 46.00 Foot of mountains, bear NW. and SE.
 Ascend.
 50.27 Rocky ravine, course SW. 15 ft. deep.
 58.70 Gulch, course SW.
 62.55 Top of ridge, bears NE. and SW.
 73.20 Top of ridge, bears NE. and SW. about 40 ft. above
 sec. cor., at 5 chs. SW. pitches off abrupt.
 78.77 The cor. of secs. 5, 6, 7 and 8.
 Land valley and bench, 46 chs.
 Soil, sandy and gravelly, 2nd rate.
 East 32.77 chs. mountainous.
 Soil, 3rd rate.
 No timber.

June 17, 1909.

- Knowing from the falling of the west Bdy. of the
 township that a random line N. $0^{\circ}1'$ E. between secs.
 5 and 6 will not strike the section corner on the
 N. Bdy. of the township within the limits allowed,
 I therefore run
 N. $0^{\circ}1'$ E. on a true line between secs. 5 and 6.
 Ascend mountains.
 19.00 Top of ridge, bears N. 38° E. and S. 38° W. about 100 ft.
 above hollow to south.
 35.10 Small shallow hollow, course SW.
 40.00 Set a basalt stone 12x12x8 ins. 8 ins. in the ground
 for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on W. face, and raise a
 mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
 This corner is on top of a small spur from ridge, and
 a bend thereof bears NW. and SW. and about 60 ft. above
 last hollow.
 Pits impracticable.
 48.00 Top of high ridge, bears S. 87° E. and S. 59° W. about
 500 ft. above valley. Descend quite rapid.
 85.17 Small ravine, 8 ft. deep, drains on course W.
 Ascend.
 87.83 Intersect the south boundary of T. 24 N., R. 24 E.,
 west 10.62 chs. from the cor. to secs. 31 and 32, of
 said township, which is a volcanic rock 7x8x9 ins.,
 above ground, marked and witnessed as described by the
 Surveyor General.