

6. Re-survey of east boundary of Tp. 46N. R. 24 E.

	North bet. secs. 1 and 6.
11.50	Ascend long gradual slope.
40.00	Set a basalt rock 18x9x5 ins., 12 ins. in the ground for 1/4 sec. cor. mkd. 1/4 on W. face and raise a mound of stone 2 1/2 ft. base, 2 ft. high W. of cor. Pits im- practicable. After diligent search no trace of the old 1/4 sec. cor. could be found.
101.50	Ridge bears E. and W.
105/24	Intersect the N. bdy. of Tp. 46 N. R. 24 E. 10.23 chs. W. of the old cor. to Tps. 46 and 47 N., Rs. 24 and 25 E. which is a basalt stone 10x9x8 ins. above ground mkd. and witnessed as described by the surveyor general. Set a chert rock 18x14x9 ins. 12 ins. in the ground for closing cor. to Tp. 46 N. Rs. 24 and 25 E., mkd. CC 46 N on S. face 25 E on E. face, and 24 E on W. face. with 6 grooves on S., E., and W. faces and raise a mound of stone 3 ft. base, 2 ft. high S. of cor. Pits im- practicable. I re-establish the old cor. to Tps. 46 and 47 N., Rs. 24 and 25 E. in its original position as a cor. to two Tps. only as follows: Set a sandstone 18x10x8 ins., 12 ins. in the ground for cor. to Tps. 47 N. Rs. 24 and 25 E. on N. bdy. of Tp. 46 N. R. 24 E. mkd. 47 N on N.E. face 24 E on N.W. face with 6 notches on N., E. and W. edges and raise a mound of stone 3 ft. base, 2 ft. high N. of cor. Pits impract- icable. Land rolling. Soil gravelly sand and rocky 4th. rate. No timber.