

10. Sub-divisions of Tp. 45 N., R. 26 E.

Chains

- 80.00 From this point Edward McGee's house bears N.59°14'E.
J. M. McGee's house bears N.38°23' E.
- 83.20 Dry channel 6ft. deep, 15 ft. wide course N.30°E.
- 96.05 Enter main channel in S. branch of Thousand Creek; a cut in clay banks 100ft. wide, 8ft. deep, course N.
- 100.00 Ascend to E. bank again.
- 104.05 Enter channel again; course N.30°E.
- 104.50 Creek 8lks. wide, 1 lk. deep, clear fresh water, course N.30°E.
- 105.60 Leave channel. Enter rolling sand hills.
- 128.10 Ridge bears S.E. and N.W.
- 137.40 Ridge bears E. and W.
- 142.20 Descend steep slope 40 ft. into
- 148.00 Sandy flat.
- 159.10 Wire fence bears E. and W.
- 170.15 N. branch of Thousand Creek 9lks. wide, 1 lk. deep, clear fresh water, course E.
- 171.15 Enter meadow of Wm. Eblin's ranch
- 179.15 Leave meadow, enter rolling sand land.
- 183.40 Wire fence bears S.85°E. and N.85°W.
- 183.52 Road bet. Denio, Oregon and Surprise Valley, Calif. bears S.85°E. and N.85°W.
- 200.30 Intersect 9th. St. Par. N. at 17.68 chs. E. from the standard cor. of secs. 32 and 33, R.26 E. which is a clay stone 12x6, 6ins. out of the ground with marks nearly obliterated, mkd. and witnessed as described by the surveyor general. I re-establish this cor. in its original position as follows;-
- Set a sandstone 17x8x5 ins., 12 ins. in the ground for standard cor. of secs. 32 and 33, Tp.46 N., R.26 E., mkd. S. C on N. with 4 grooves on E. and 2 grooves on the W. face and raise a mound of stone 2½ ft. base, 2 ft. high N. of cor. Pits impracticable.
- Set a chert rock 17x10x7 ins., 12 ins. in the ground for