

Survey of Exteriors of T. 17 N., R. 43 E.

Chains

25.60 On brow of peak

27.00 Descend at 15°

32.40 Hollow, course N.,

34.60 At head of deep canon, course N.,

40.00 Set a granite stone 24x6x4 ins., 18 ins. in the ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on N. face. Dig pits 18x18x12 ins. E. and W. of cor. 3 ft. dist., and raise a mound of earth $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

45.90 Canon, course NW.,

46.90 Canon, course NW.,

48.00 Ascend steep mtn.,

52.50 In ravine on mtn. side, course NW.,

Enter a forest of blighted pines

73.80 Base of cliff

79.05 Rocky summit, bears NE. and SW.,

80.00 Set slate rock 30x16x6 ins. 22 ins. in the ground for cor. of secs. 35, 36, 1 and 2, marked with 5 notches on the W. and 1 notch on the E. edge, and raise a mound of stone 2ft base, $1\frac{1}{2}$ ft. high, W. of cor. Pits impracticable.
Land, mountainous.
Soil, stony, third rate.
Timber, blighted pines and sagebrush.
Mountainous land, covered with timber, difficult to survey, 80 chs.

E. bet. secs. 36 and 1

Descend

2.00 Descend at 26°

7.00 Descend at $37\frac{1}{2}$ °

18.00 Descend at 32°

20.00 Descend at 26°

40.00 Set slate rock 20x10x3 ins., 15 ins. in the ground for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on N. face and raise a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high N. of cor. Pits impracticable.