

Survey of E. Boundary of T. 18 N., R. 43 E.

Chains

- 40.00 Set a slate rock 15x8x4 ins. 10 ins. in the ground for $\frac{1}{4}$ sec. cor. to sec. 12, marked $\frac{1}{4}$ on W. face, and dig pits 18x18x12 ins., N. and S. of cor. 3 ft. dist., and raise a mound of earth $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high W. of cor.
- 45.80 Ravine, course NW.,
- 59.50 Ravine, course NE.,
- 63.30 Set a granite stone 20x8x8 ins., 15 ins. in the ground for cor. to secs. 6 and 7, marked with 5 notches on S. and 1 notch on N. edge and raise a mound of stone 2 ft. base, $1\frac{1}{2}$ ft high E. of cor. Pits impracticable.
- 63.90 Ravine, course E.,
- 80.00 Set a granite stone 24x14x10 ins., 18 ins. in the ground for cor. to secs. 1 and 12, marked with 5 notches on S. and 1 notch on N. edge, and raise a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high W. of cor. Pits impracticable.
- Land, mountainous
- Soil, stony, second rate.
- Timber, pine, cedar, and sagebrush.
- Mountainous land, very difficult to survey, 80 chs.

- N. on E. bdy. of sec. 1.
- 3.25 Road, in canon, bears NW. and SE.,
- 17.00 Ridge, bears E. and W.,
- 23.30 At W. side of ledge of rock, which bears N. and S., I set a granite stone 18x6x6 ins., 12 ins. in the ground for $\frac{1}{4}$ sec. cor. to sec. 6, marked $\frac{1}{4}$ on W. face, and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high W. of cor. Pits impracticable.
- 27.50 Summit of rocky ridge, bears E. and W.,
- 40.00 Set a granite stone 24x10x6 ins., 18 ins. in the ground, for $\frac{1}{4}$ sec. cor. to sec. 1, marked $\frac{1}{4}$ on W. face, and raise a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high W. of cor. Pits impracticable.