Survey of N. Bdy. of T. 18 N., R. 44 E.

Chains	Mountainous land, very difficult to survey, 80 chs.
	W. on N. bdy. of sec. 6.
.60	Prospect holes
20.00	Ravine, course S.,
25.50	On S. side of ridge, bears E. and W.,
33.23	Trail over mtn., bears NW. and SE.,
35.00	Ravine, course S.,
38.88	Set a granite stone 15x14x10 ins., 10 ins. in the ground for ¼ sec. cor. to sec. 31, marked ¼ on N. face and raise a mound of stone 2 ft. base, 1½ ft. high N. of cor. Pits impracticable.
40.00	Set a granite stone 20x8x6 ins. 15 ins. in the ground, for ¼ sec. cor. to sec. 6, marked ¼ on N. face, and raise a mound of stone 2 ft. base, 1½ ft. high N. of cor. Pits impracticable.
42.43	Ridge, bears N. and S.,
45.20	Ridge of rock
60.00	Ravine, course S.,
61.33	Ravine, course S.,
67.72	Enter pine trees
75.40	Leave the trees
75.80	Ridge, bears N. and S.,
82.67	Intersect W. bdy. of sec. 31, 14.59 chs. S. 0° 23' W., from the cor. originally set for cor. of Tps. 18 and 19 N., Rs. 43 and 44 E. Here I set a granite stone 24x14x3 ins., 18 ins. in the ground, for the SW. cor. of T. 19 N., R. 44 E., marked with 6 notches on N. and E. edges, and raise a mound of stone 2 ft. base, 1½ ft. high NE. of cor. Pits impracticable.
	I then correct the markings on the stone originally set at the cor. of Tps. 18 and 19 N., Rs. 43 and 44 E., making it the SE. cor. to T. 19 N., R. 43 E., marked with 6 notches on N. and W. edges, and raise a mound of stone 2 ft. base, 1½ ft. high NW. of cor. Pits impracticable.