

Survey of Boundary of T. 14 N., R. 41 E.

Chains	
	South boundary.
	E. bet. secs. 1 and 36.
1.50	Summit of ridge, bears N.,
6.00	Leave trees.
14.45	Ravine, course NE.,
27.75	Ravine, course N.,
32.85	Summit of N. end of spur, bears N.,
35.40	Mahogany thicket 1 ch. wide.,
40.00	Set a limestone 16x6x6 ins. 12 ins. in the ground, for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on N. face and raise a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high N. of cor. Pits impracticable. Whence A pine, 9 ins. diam., bears N. $20^\circ 10'$ W. 106 lks. dist. marked $\frac{1}{4}$ S. 36 B.T.
	A pine, 10 ins. diam., bears S. $75^\circ 45'$ E. 106 lks. dist., marked $\frac{1}{4}$ S. 1 B.T.
44.10	Marysville canon, course NW.,
48.13	Marysville creek, 3 lks. wide $4\frac{1}{2}$ lks. deep, course NW.,
50.31	E. side of road in canon, bears N. 35° W.,
53.00	Leave canon, enter trees.
62.50	Bank of ravine, course NW.,
63.50	In ravine, course NW.,
80.00	Set a granite stone 20x14x8 ins. 15 ins. in the ground for cor. to T. 13 and 14 N., Rs. 41 and 42 E, marked with 6 notches on N, E., S. and W. edges and 14 N. on NE. face, 41 E. on NW. face, 13 N. on SW. face, and 42 E. on SE. face. and raise a mound of stone 2 ft. base $1\frac{1}{2}$ ft. high S. of cor. Pits impracticable. Whence A pine, 6 ins. diam., bears N. 61° W. 6 lks. dist., marked T. 14 N. R. 41 E., S. 36 B.T.
	A pine, 5 ins. diam., bears N. 46° E. 36 lks. dist., marked T. 14 N. R. 42 E., S. 31 B.T.
	A pine, 12 ins. diam., bears S. 72° E., 30 lks. dist., marked T. 13 N., R. 42 E. S. 6 B.T.
	No tree available for sec. 1.