

Subdivision of T. 10 S., R. 47 E.

Chains. Survey of the subdivision of this township commenced April 15, 1909, and executed with a C. L. Berger and Sons Mountain Transit No. 4; the horizontal limb having two double verniers placed opposite to each other and reading to 30" of arc.

At the cor. of secs. 35 and 36 heretofore described, at 7:50 p.m. l.m.t. I observe Polaris, in accordance with instructions in the Manual, and mark the line thus determined by a tack driven in a wooden peg set in the ground 5 chains north of my station.

April 16, at 7:45 A.M., I lay off the azimuth of Polaris 1°16' to the east, and thence I run,

N.0°01'W. bet. secs. 35 and 36.
Over gradually descending land.

40.00 Set a basalt stone 15 x 12 x 8 ins., 10 ins. in the ground, for 1/4 sec. cor. marked 1/4 on W. face; and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor. Pits impracticable.

80.00 Set a basalt stone 15 x 12 x 10 ins., 10 ins. in the ground, for cor. of secs. 25, 26, 35 and 36, marked with 1 notch on S. and E. edges; and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor. Pits impracticable.
Land rolling.

Soil, sandy and rocky; 3rd rate.

Greasewood and sagebrush undergrowth.

N.89°42'E. on a random line between secs. 25 and 36.

40.00 Set temp. 1/2 sec. cor.

79.96 Intersect E. bdy. of Tp. 3 lks. S. of cor. to secs. 25, 36, 30 and 31, heretofore described.

Thence I run

S.89°41'W. on a true line bet. secs. 25 and 36.

Over gradually descending land.

22.50 Road, bears S.70°E. and N.70°W.

39.98 Set a basalt stone 16 x 12 x 6 ins., 11 ins. in the