

Retracement and reestablishment of a portion of  
the East line of Tps. 34 N., R. 67 E.

(13)

- Chains. April 24: At 8h.0m. a.m. l.m.t. I set off:  
40°50' on the lat arc and 12° 49' N. on the decl. arc,  
and determine a true meridian at the cor. of tps. 34 and  
35 N., R. 67 E., a stone previously described.
- Thence I run South
- Making careful search at every 40 and 80 chs., but  
finding no sec. cors. until
- 320.60 Pass 2.25 chs. E. of the cor. of secs. 24 and 25,  
T. 34 N., R. 67 E. The course of this line bet. the  
corners is therefore S. 0° 24' W.
- A post 4 ins. square, standing 2 ft. out of the  
ground marked and witnessed as described by the Surveyor  
General.
- I destroy markings referring to Tp. 34 N., R. 68E.
- April 24, 1909.
- 
- April 25: Thence I run N. 0° 24' E. on the E. line  
sec. 24.  
Across rolling land
- 40.08 Set a lime stone 15x10x10 ins., 10 ins. in the  
ground for  $\frac{1}{4}$  sec. cor. marked  $\frac{1}{4}$  on the W. face; dig pits  
18x18x12 ins., N. and S. of cor., 3 ft. dist. and raise  
mound of earth, 3 1/2 ft. base, 1 1/2 ft. high W. of cor.
- 57.60 Dry wash, course W.
- 71.90 Dry wash, course W.
- 72.50 Road bears E. and W.
- 80.15 Set a lime stone 18x10x7 ins., 12 ins. in the ground  
for cor. of secs. 13 and 24, marked with 3 notches on the  
N. and S. edges; dig pits 24x24x12 ins. in each sec. 6  
ft. dist., raise mound of earth 4 ft. base, 2-ft. high,  
W. of cor.
- Land rolling,
- Soil gravelly, 3rd rate.
- Growth of sage brush and bunch grass.
-