

(2)

Subdivision of T.35 N.R.69 E.

chains	S.0°2'E.bet.secs.34 and 35
	Across level land
40.00	Set a limestone 20x10x3 ins.,15 ins.in the ground for $\frac{1}{4}$ sec.cor.marked $\frac{1}{4}$ on the W.face,dig pits 18x18x12 ins., N.and S.of stone 3 ft.dist.and raise mound of earth $3\frac{1}{2}$ ft.base, $1\frac{1}{2}$ ft.high,W.of cor.
80.00	The cor.of secs.2-3-34 and 35,established by me March 30-1909,as follows:- Deposited a quart of broken glass 12 ins.in the ground for cor.of secs.2-3-34 and 35:dug pits 18x18x12 ins.,in each sec.4 ft.dist.and raised mound of earth 4 ft.base 2 ft.high,over deposit. In SE.pit drove a pine stake 2 ft.long,2 ins.square, 12 ins.in the ground,marked T 35 N S 35 on NE., R 69 E S 2 on SE., S 3 on SW.and S 34 on NW.face,with 2 notches on E.and 4 notches on W.edges. Land level Soil sandy and alkaline, 3rd.rate. Undergrowth of grease-wood.
	N.0°1'W.bet.secs.25 and 26
	Across level land
20.00	SW.point of a butte bears N.35°20'E.
40.00	Set a conglomerate stone 18x10x8 ins.,12 ins.in the ground for $\frac{1}{4}$ sec.cor.marked $\frac{1}{4}$ on the W.face,dig pits 18x18 x 12 ins.,N.and S.of stone 3 ft.dist.and raise mound of earth $3\frac{1}{2}$ ft.base, $1\frac{1}{2}$ ft.high,W.of cor. Whence SW.point of same butte bears N.70°E.
59.00	Road bears N.75°E.and S.75°W.
70.00	Road bears S.75°E.and N.75°W.
80.00	Set a conglomerate stone 26x14x12 ins.,20 ins.in the ground for cor.of secs.23-24-25 and 26,marked with