

(16)

Subdivisions of T.34 N.R.68 E. 2

chains

55.00 Ridge, bears S.60°W. and N.60°E., descend  
 70.00 Draw, course S.70°W., ascend  
 85.00 Ridge, bears S.70°W. and N.70°E., descend  
 92.82 Intersect the W. bdy. of the Tp., N.0°24'E. 3.64 chs. from  
 the cor. of secs. 1 and 12. A stone previously described.  
 Set a lime stone 20x10x8 ins., 15 ins. in the ground  
 for closing cor. of secs. 6 and 7, marked C.C. on E., with  
 1 groove on N. and 5 grooves on S. face, and raise a mound  
 of rock 4 ft. base, 3 ft. high, E. of cor. Pits impracticable  
 Land rolling  
 Soil gravelly, 3rd. rate.  
 Scattering growth of pine and cedar timber with an  
 undergrowth of sage brush and bunch grass

---

S.0°4'E. bet. secs. 7 and 8  
 Ascending rolling hills, through scattering pine and  
 cedar timber.  
 2.00 Ridge, bears N.45°E. and S.45°W., descend  
 7.00 Draw, course, West, ascend  
 16.00 Ridge, bears E. and W., descend  
 32.00 Draw, course W., ascend  
 36.00 Ridge, bears E. and W., descend  
 40.00 Set a lime stone 15x12x10 ins., 10 ins. in the ground  
 for  $\frac{1}{4}$  sec. cor., marked  $\frac{1}{4}$  on the W. face, dig pits 18x18x12  
 ins., N. and S. of stone 3 ft. dist. and raise mound of earth  
 $3\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.  
 45.00 Draw, course S.60°W., ascend  
 50.00 Ridge bears S.60°W. and N.60°E., descend  
 54.00 Draw, course S.75°W., ascend  
 80.00 Set a lime stone 16x10x8 ins., 11 ins. in the ground, for  
 cor. of secs. 7-8-17 and 18, marked with 4 notches on S. and  
 5 notches on E. edge, dig pits 18x18x12 ins., in each sec.  
 $5\frac{1}{2}$  ft. dist. and raise a mound of earth 4 ft. base, 2 ft. high  
 W. of cor., east. W. side  
 Land rolling  
 Soil gravelly, 3rd. rate