' S. bdy. T 25 N, R 64 E.

Chains

this tp. and commencing the sub-division, I run west on a blank line and at intervals of 40.00 chs. I search diligently for corners, but find none till I have run 4 miles when I find the cor. to secs. 4,5,32 and 33, falling 93 lks. north of my line.

At 5 miles I find the cor. to secs. 5,6,31 and 32, falling 1.17 chs. north of my line.

At 5 miles 79.86 chs. I find the cor. to Tps. 24 and 25 N,Rs. 63 and 64 E. Mt. Diablo B. and M., falling 1.40 chs. to the north of my line.

As T 24 N,R 64 E, has been sub-divided I do not disturb the alinement or position of the corners found but resurvey the south bdy. of T 25 N,R64 E, as follows:

The old corner of Tps. 24 and 25 N, Rs. 63 and 64 E is a juniper stake badly decayed and the markings nearly obliterated. I destroy all traces of the old corner and re-establish it at the same point as follows:

Set a limestone 15/9/5 ins.,10 ins, in the ground for cor.of Tps. 24 and 25 N.Rs.63 and 64 E, marked

25 N on N.E.,

64 E on S.E.,

24 N on S.W., and

63 E on N.W. face and with 6 notches on each edge; dig pits 24/24/12 ins., on each line N.E. and W., 4 ft. and S. of stone 8 ft. dist.; and raise a mound of earth 5 ft. base, $3\frac{1}{2}$ ft. high, S. of cor.

Thence I run

S 89°50'E bet. secs. 31 and 6.

Over level land.

10.20 Road, bears N. and S.

39,86 Set a limestone 14/9

Set a limestone 14/9/4 ins., 10 ins. in the ground for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on N. face; dig pits 18/18/12 ins. E. and W. of stone 3ft. dist.; and raise a mound of earth $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high N. of cor.

79,86 The old cor. to secs. 5,6,31 and 32.