

Resurvey of ^W Boundary of T. 38 N. R. 50 E.

Chains.	
	rebuild as follows: Set a rhyolite stone 16x10x8 ins. 11 ins. in the ground for cor. of secs 1 and 12, marked with 5 notches on the S. and 1 notch on the N. edge and raise a mound of stone 2 ft. base 1½ ft. high W. of cor. Pits impracticable.
	Land, mountainous.
	Soil, stony, third rate.
	Timber, sagebrush .
	Mountainous land, very steep. 81.14 chains.
	Aug. 4th. 1909.
	Aug. 5th. 1909.
	At 6h. 56 m. A.M. 1.m.t. I set off 17° 5' N. on the decl. arc and 40° 18' on the lat. arc and determine a meridian with the solar at the cor of secs. 1 and 12, Thence I run, N. on E. bdy of sec. 1,
8.10	Draw, course E.
17.20	Spur, bears E. and W.
19.90	Draw. course E.
32.00	Nose of Ridge, bears E. and W.
36.05	Draw, course E. bns
40.05	The old ¼ sec. cor. A basalt stone 16x10x6 ins. lying loose with mound scattered. I destroy all traces of the old ¼ sec. cor. and in the same place I rebuild as follows: Set a basalt stone 16x10x6 ins. 11 ins. in the ground for ¼ sec. cor. marked ¼ on W. face and raise a mound of stone 2 ft, base 1½ ft. high W. of cor. Pits impracticable.
43.00	Ridge, bears E. and W.
54.10	Draw, course E.
56.80	Spur, bears E. and W.
61.00	Draw, course E.
62.00	Nose of spur, bears NE. and SW.
63.00	Draw, course NE.
72.00	Ridge, bears NE. and SW.
79.30	Draw, course NE.
80.05	The cor. to Tps. 28 and 29 N. R's. 49 and 50 E. in good condition. A basalt stone 8x6x6 ins. above ground