

Subdivisions of T. 29 N. R. 51 E.

Chains.

4 notches on the S. and 1 notch on the E. edge; dig pits 18x18x12 ins. in each sec. $5\frac{1}{2}$ ft. dist. and raise a mound of earth 4 ft. base 2 ft. high W. of cor.

Land, rolling.

Soil, sandy second rate.

Timber, sagebrush.

Rolling land, 80.00 chs.

From the condition of the E. bdy. and the closing on the last mile to the E. I find that closing corrs. are necessary for the next two miles to the E. or the lines bet. secs. 12 and 13, and secs. 1 and 12. Hence I run these lines East as random lines.

East on a random line bet. secs. 12 and 13.

40.00 Set temp $\frac{1}{4}$ sec. cor.

79.77 Intersect N. and S. line 1.32 chs. N. of the cor. of secs. 7, 12, 13 and 18. I set a kaolin stone 18x10x8 ins. 12 ins. in the ground, for closing cor. of secs. 12 and 13, marked CC on the W. with 2 grooves on the N. and 4 grooves on the S. face; dig pits 24x18x12 ins. crosswise on each line N. and S. 3 ft. and W. of stone 7 ft. dist. and raise a mound of earth 4 ft. base 2 ft. high W. of cor.

I now change the marks and accessories on the cor. of secs. 7, 12, 13 and 18 to refer to secs. 13 and 18 only, by reestablishing the cor. as follows: I destroy pits and mound already built and dig pits 24x24x12 ins. in each sec. 6 ft. dist. and raise a mound of earth 4 ft. base 2 ft. high E. of cor.

Thence I run W. on a true line bet. secs. 12 & 13.

19.72 Draw, course SE.

39.88 $\frac{1}{2}$ Set a rhyolite stone 18x10x4 ins. 12 ins. in the ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on N. face; dig pits 18x18x12 ins. E and W. of stone 3 ft. dist. and raise a mound of earth $3\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N. of cor.

56.77 Draw, course NE.

57.77 Spur, bears N. and S.