

Survey of the W. bdy. of T 34 N, R 23 E, Mt. Diablo B. and M.

Chains.

June 12, 1910.

I begin at the cor. of Tps. 33 and 34 N., Rs. 22 and 23 E, Mt. Diablo B. and M., which corner is a granite stone 15-8 ins. by 14 ins. above ground. Firmly set and marked and witnessed as described by the Surveyor General.

Thence I run

N. bet. secs. 31 and 36.

Over mountainous land.

9.50 Ravine, course S.W. Begin ascending E. slope of mountain.

24.60 Small ravine, course S.E.

30.00 Begin ascent of rocky ridge.

40.00 Set a granite stone, 30-16-4 ins., 20 ins. in the ground for 1-4 sec. cor., marked 1-4 on the W. face and raise a mound of stone 2 ft. base, 1 1-2 ft. high W. of cor. Pits impracticable.

40.45 High rocky ridge, bears E. and W. Begin descending.

60.00 Enter grassy flat.

80.00 Set a granite stone, 16-10-4 ins., 12 ins. in the ground for cor. of secs. 25, 30, 31 and 36, marked with 1 notch on S. edge and 5 notches on N. edge. Raise a mound of stone 2 ft. base, 1 1-2 ft. high W. of cor.

Pits impracticable.

Land, mountainous.

Soil, rocky. 4th. rate.

Vegetation, sagebrush and bunchgrass.

Mountainous land, 80.00 chs.

N. bet secs. 25 and 30.

Over mountainous land.

6.30 Leave grassy flat.

30.00 Ridge, bears E. and W. Begin descending .

40.00 Set a granite stone, 18-12-5 ins., 12 ins. in the ground for 1-4 sec. cor., marked 1-4 on the W. face and raise a mound of stone 2 ft. base, 1 1-2 ft. high W. of cor.

Pits impracticable.

41.00 Creek, 3 links wide, course S.W.