

Retracement of the W. bdy. of T 37 N, R 22 E, Mt . Diablo B. and M.

Chains.

Mountainous land, 22.00 chs.

N 0° 13' E bet. secs. 7 and 12.

Over rolling land, sloping to the N.

40.23 The 1-4 sec. cor., a basalt stone, 10-6 ins. by 12 ins. above ground. Firmly set and marked and witnessed as described by the Surveyor General.

80.38 The cor. of secs. 1, 6, 7 and 12. A basalt stone, firmly set in the ground and marked and witnessed as described by the Surveyor General. I destroy all traces of this cor. and its accessories and re-establish it at the same point as follows:

Set a basalt stone, 20-16-12 ins., 14 ins. in the ground for cor. of secs. 1 and 12, marked with 5 notches on the S. and 1 notch on the N. edge and raise a mound of stone 2 ft. base, 1 1-2 ft. high W. of cor.

Pits impracticable.

Land, rolling.

Soil, rocky. 4th. rate.

Vegetation, sagebrush and bunchgrass.

N 0° 13' E bet. secs. 1 and 6.

Over rolling land sloping to the N.

40.40 The 1-4 sec. cor., a basalt stone, 8-5 ins. by 11 ins. above ground, firmly set and marked and witnessed as described by the Surveyor General.

80.70 The cor. of Tps. 37 and 38 N, Rs. 21 and 22 E. A basalt stone firmly set in the ground and marked and witnessed as described by the Surveyor General. I destroy all traces of this cor. and its accessories and re-establish it at the same point as follows:

Set a basalt stone, 24-16-14 ins., 16 ins. in the ground for cor. of Tps. 37 and 38 N, R 21 E, marked 37 N on S.W. and 21 E on N.W. face and with 6 notches on N. and W. edges and raise a mound of stone 2 ft. base, 1 1-2 ft. high W. of cor.

Pits impracticable.