

## Chains.

tablish it at the same point as follows:

Set a basalt stone, 16-12-7 ins., 12 ins. in the ground for cor. of secs. 18 and 19, marked with 3 notches on the N. and S. edges and raise a mound of stone 2 ft.

base, 1 1-2 ft. high E. of cor.

Pits impracticable.

Land, mountainous.

Soil, rocky. 4th. rate.

Vegetation, sagebrush and bunchgrass.

Mountainous land, 81.06 chs.

S. bet. secs. 19 and 24.

Ascending over mountain land.

20.45 High, rocky ridge, bears E. and W. Begin descending.

31.10 Ravine, course W. Begin ascending.

40.50 The 1-4 sec. cor., a basalt stone, firmly set in the ground marked, witnessed and of the dimensions described by the Surveyor General.

47.45 Ridge, bears E. and W. Begin descending.

51.10 Small ravine, course W. Begin ascending.

56.90 Ridge, bears E. and W. Begin descending.

81. 06 The cor. of secs. 19, 24, 25 and 30.

Land, mountainous.

Soil, rocky. 4th. rate.

Vegetation, sagebrush and bunchgrass.

Mountainous land, 81.06 chs.

July 10, 1910.

July 13, 1910.

Subdivision of T 37 N, R 22 E, Mt. Diablo B. and M.

Since the S. bdy. is defective in alinement and measurements I establish a sectional correction line, as follows:

From the cor. of secs. 25, 30, 31 and 36 I run:

W. on a true line bet. secs. 25 and 36

Over mountainous land.

5 .70 Ridge, bears N.E. and S.W. Begin descending.