

Subdivision of T 37 N, R 22 E, Mt. Diablo B. and M.

Chains.

W. on a true line bet. secs. 29 and 32.

Ascending over rolling land.

19.80 Ridge, bears N. and S. Begin descending.

40.00 Set a basalt stone 24-9-4 ins., 16 ins. in the ground for 1-4 sec. cor., marked 1-4 on the N. face and raise a mound of stone 2 ft. base, 1 1-2 ft. high N. of cor. Pits impracticable.

47.50 Road, bears N. and S.

57.15 Rocky ridge, bears N. and S. Begin descending.

65.40 Ravine, course N.W.

80.00 Set a basalt stone 18-12-6 ins., 12 ins. in the ground for cor. of secs. 29, 30, 31 and 32. Marked with 1 notch on the S. and 5 notches on the E. edge and raise a mound of stone 2 ft. base, 1 1-2 ft. high W. of cor. Pits impracticable.

Land, rolling.

Soil rocky. 4th. rate.

Vegetation, sagebrush and bunchgrass.

W. on a true line bet. secs. 30 and 31.

Ascending over mountainous land.

8.00 Enter mahogany trees.

10.00 Ridge, bears N. and S. Begin descending abruptly.

19.85 Leave mahogany thicket.

21.95 Creek, 3 links wide, course N. Begin steep ascent.

40.00 Set a basalt stone 15-9-7 ins., 11 ins. in the ground for 1-4 sec. cor., marked 1-4 on the N. face and raise a mound of stone 2 ft. base, 1 1-2 ft. high N. of cor. Pits impracticable.

43.20 Ridge, bears N. and S. Begin descending.

60.10 Ravine, course N. Begin ascending.

65.90 Enter mahogany thicket.

72.20 Intersect the W. bdy. of the Tp. at N 0° 13' E, 14.46 chs. from the cor. of secs. 25 and 35.

Set a granite stone 18-10-6 ins., 12 ins. in the ground for closing corner of secs. 30 and 31, marked C C on the