

Subdivision of T. 37 N., R. 22 E., Mt. Diablo E. and M.

Chains

- W. on a true line bet. secs. 19 and 30  
 Descending over mountainous land.
- 4.20 Creek, 4 links wide, course N. Begin ascending.
- 10.60 Ridge, bears N. and S. Begin descending.
- 18.37 Ravine, course N. Begin ascending.
- 30.00 Ridge, bears N. and S. Begin descending.
- 37.30 Ravine, course N. Begin ascending.
- 40.00 Set a basalt stone, 18-8-8 ins. , 12 ins. in the ground  
 for 1-4 sec. cor., marked 1-4 on the N. face and raise  
 a mound of stone 2 ft. base, 1 1-2 ft. high N. of cor.  
 Pits impracticable.  
 Ascend over mountainous land.
- 71.76 Intersect the W. bdy. of the Tp. at N 0 13'E, 13.65 chs.  
 from the cor. of secs. 24 and 25.  
 Set a basalt stone 21-14-5 ins., 14 ins. in the ground  
 for closing corner of secs. 19 and 30, marked C C on  
 E. face; with 2 grooves on S. and 4 grooves on N. face  
 and raise a mound of stone 2 ft. base, 1 1-2 ft. high  
 E. of cor.  
 Pits impracticable.  
 Land, mountainous.  
 Soil, rocky. 4th. rate.  
 Vegetation, sagebrush and bunchgrass.  
 Mountainous land, 71.70 chs.

July 27, 1910.

July 28, 1910.

N 0° 4' W bet. secs. 19 and 20

Ascending over mountainous land.

- 21.00 Cliffs, bear N.W. and S.E. Begin descending.
- 35.00 Ravine, course W. Begin ascending.
- 40.00 Set a basalt stone 17-10-9 ins., 13 ins. in the ground  
 for 1-4 sec. cor., marked 1-4 on the W. face and raise  
 a mound of stone 2 ft. base, 1 1-2 ft. high W. of cor.  
 Pits impracticable.  
 Continue across rolling ground.
- 80.00 Set a basalt stone 21-14-5 ins., 14 ins. in the ground